

# Nilamtec A2 Series

## IS IT A RUGGED SMARTPHONE?

**A2 IS MORE THAN A RUGGED SMARTPHONE, IT IS A TOOL FOR PROFESSIONAL USER TO IMPROVE THEIR PRODUCTIVITY.**

**A2 IS FULLY COMPATIBLE WITH A1, BUT HAS A MORE POWERFUL CPU, MORE MEMORY, AND BETTER DISPLAY. IT IS PERFECT FOR RUNNING COMPUTING POWER DEMANDING FIELD APPLICATIONS.**

The Nilamtec A2 is a rugged handheld designed for Construction, GIS, Environmental Management, Public and Utility Field applications. A2 can be operated in either Kiosk or Mobile Mode. There are choices of A2 models to meet the GNSS accuracy requirements of location sensitive applications.

## Kiosk Mode VS Mobile Mode

A2 is a full functioned Android smartphone. A2 can run Android Apps just as same as the Android smartphone in the market.

A2 can be also used as a kiosk device. For kiosk applications, A2 can be operated without battery, and the device supports auto power up. Once the power supply to A2 is on, A2 will be powered up automatically, and run the apps for you. A2 is an ideal product for construction site gate access control and remote monitoring.

## GNSS Accuracy

The GNSS performance of A2 is better than the standard smartphones. A2 supports GPS, GLONASS and Beidou constellations. In addition to the strong GNSS reception power, A2 has choice of

GNSS accuracy receiver options, which is from <1.5 m RMS standalone real time GNSS to cm grade RTK built-in receiver. You can easily find a right model to meet the challenges of positioning accuracy of your field applications.

## Reliability and Efficiency in The Field

You can take A2 as a smartphone to the field without worry about dust, water, damage caused by dropping the phone, high or low temperature, and long operation hour.

- A2 provides IP67 rated protection from dust and water ingress
- The operating temperature of A2 is from -20°C to +60°C. A2 supports you in both cool winter and hot summer.
- User replaceable 4000 mAh battery allow you keep working all day long in remote sites.
- Integrated 13M pixel rear camera allows you take sharp photos for your information sharing.
- 5.5" FHD AMOLED screen provides bright and easy to read display.

## Not Just a Rugged Smartphone. It Is a Tool to Improve Your Productivity

It is a smart investment in A2. A2 helps you to improve your field operation efficiency in Worker Attendance Taking, E-work flow management, GIS data collection and more.



Global Distributor:  
Strobus (Far East) Limited  
Unit 2602-3, BEA Tower, Millennium City 5,  
418 Kwun Tong Road, Kwun Tong, Hong Kong.  
T: +852-2690-3773, F: +852-2690-3030  
Email: [info@strobus.com.hk](mailto:info@strobus.com.hk), URL: [www.strobus.com.hk](http://www.strobus.com.hk)

Your Local Distributor:

# Nilamtec A2 Series

## STANDARD FEATURES

### SYSTEM

- Integrated LTE cellular data, voice, and text capability
- 13MP rear camera, 5MP front camera
- High sensitivity GNSS receiver and antenna
- Bluetooth 4.1
- WIFI IEEE802.11 a/b/g/n/ac, 2.4GHz and 5GHz
- Capacitive multi-touch 5.5" FHD AMOLED 1920x1080 Gorilla Glass Screen, 450cd/m<sup>2</sup> Brightness
- 4000 mAh long lasting, user replaceable, wide temperature range battery
- Qualcomm MSM8953 Octa core 2.2GHz Processor
- 4GB RAM, 64GB Flash Memory
- Support Micro SD card
- Dual SIM, Dual Standby

### OPERATING SYSTEM

- Android 8.1

### COMMUNICATIONS NETWORK

- GSM:850/900/1800/1900,
- EVDO: BC0,
- WCDMA: B1/B2/B5/B8,
- TD-SCDMA: B34/B39
- TDD-LTE: Band38/Band39/Band40/Band 41,
- FDD-LTE: Band1/Band3/band4/band5/B and7/band8/band17/band20/band28
- WIFI: IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz
- Bluetooth: Bluetooth 4.1
- USB: USB 2.0, Type C
- NFC

- Extended Pogo Pin Interface: USB, UART, I<sup>2</sup>C, GPIO, Power Charging

### POWER MANAGEMENT

- Battery: 4000 mAh wide temperature range, user replaceable Li-ion battery
- Fast Charging: Support Qualcomm QC 3.0 (need to work with QC 3.0 charger)
- Power on: Support auto power on

### SENSORS

G Sensor, Temperature Sensors, Gyroscope, Light Sensor, E-Compass

### TECHNICAL SPECIFICATIONS

#### PHYSICAL

- Size: 164.9 x 83.5 x 13 mm
- Weight: approx. 198 g (including battery, the weight various with models)
- Processor: Qualcomm MSM8940 Octa core 1.4GHz
- Memory: 4GB RAM, 64GB Flash
- User Interface: Hard Power, Volume up/down Keys
- Battery: 4000 mAh, user replaceable, wide temperature range Li-ion battery

#### ENVIRONMENTAL

##### Temperature:

- Operating: -20 °C to +60 °C
- Storage: -30 °C to +70 °C

##### Humidity:

- 95% non-condensing

##### Dust and Water Proof:

- IP67

##### Drop Resistance:

- 1.2 m free drop to concrete

### INPUT/OUTPUT

Extended Memory: Micro SD card (T card)

##### Display:

Damage-Resistant Gorilla Glass  
5.5" AMOLED Capacitive Multi-touch screen  
1920x1080 Pixel resolution  
450 cd/m<sup>2</sup> brightness

##### Audio:

Built-in speaker and microphone  
Support USB-C type corded microphone

##### Camera:

Rear Camera: 13 MP with flash light  
Front Camera: 5 MP

##### Sensors:

G Sensor, Temperature Sensors, Gyroscope, Light Sensor, E-Compass

### GNSS SYSTEM

Models	A2	A2T	A2P
Internal Patch Antenna, L1, B1, G1, 72 channels	Yes	Yes	Yes
Integrated Real Time SBAS Dual Constellation System, GPS/GLONASS or GPS/BEIDUO	Yes	Yes	Yes
External GNSS Antenna	No	No	No
Android Location Services	Yes	Yes	Yes
NMEA output	Yes	Yes	Yes
Raw Data output	No	Yes	Yes
RTK	No	No	Yes
Standalone GNSS Accuracy (horizontal RMS)	<1.5 M	<1.5 M	<1.5 M
RTK Accuracy (horizontal RMS)	N/A	N/A	<5 CM



Global Distributor:  
Strobus (Far East) Limited  
Unit 2602-3, BEA Tower, Millennium City 5,  
418 Kwun Tong Road, Kwun Tong, Hong Kong.  
T: +852-2690-3773, F: +852-2690-3030  
Email: [info@strobus.com.hk](mailto:info@strobus.com.hk), URL: [www.strobus.com.hk](http://www.strobus.com.hk)

Your Local Distributor: